



Osaka 3		Длина без боковин	Рабочая температура	Площадь выкладки	Полезный объём
		(мм)	(°C)	(м ²)	(дм ³)
65	200	1250	-1°C / +1°C +0°C / +2°C +2°C / +4°C	2,30	717
		1875		3,45	1076
		2500		4,60	1435
		3750		6,90	2152
	216	1200		2,30	774
		1875		3,45	1162
		2500		4,60	1549
		3750		6,90	2323
70	200	1250		2,61	816
		1875		3,92	1224
		2500		5,22	1631
		3750		7,83	2447
	216	1200		2,61	881
		1875		3,92	1321
		2500		5,22	1762
		3750		7,83	2642
75	200	1250		2,92	914
		1875		4,39	1371
		2500		5,85	1828
		3750		8,77	2742
	216	1200		2,92	987
		1875		4,39	1481
		2500		5,85	1974
		3750		8,77	2962
80	200	1250	3,24	1012	
		1875	4,85	1518	
		2500	6,47	2024	
		3750	9,71	3037	
	216	1200	3,24	1094	
		1875	4,85	1640	
		2500	6,47	2187	
		3750	9,71	3281	
85	200	1250	3,30	1029	
		1875	4,95	1543	
		2500	6,60	2058	
		3750	9,90	3087	
	216	1200	3,30	1110	
		1875	4,95	1665	
		2500	6,60	2221	
		3750	9,90	3331	
90	200	1250	3,36	1046	
		1875	5,04	1568	
		2500	6,72	2091	
		3750	10,08	3137	
	216	1200	3,36	1127	
		1875	5,04	1691	
		2500	6,72	2254	
		3750	10,08	3381	

